

Storage Synology NAS DS-923+ 4-Bay /DDR4  
ECC/ 2x USB3.2

Šifra: 14197  
Kategorija proizvoda: NAS uređaji  
Proizvođač: Synology

Cena: **90.388,00** rsd.



|   |  |
|---|--|
| Storage System Type:                    | NAS  |
| Form Factor:                            | Tower  |
| Device Location:                        | External   |
| Built-in Devices:                       | LED Indicator  |
| Networked Storage Device Features:      | AES Encryption   |
| Expansion Slot:                         | M.2 (x2)   |
| CPU:                                    | AMD Ryzen R1600  |
| Internal Clock Rate:                    | 3.1 GHz  |
| CPU Installed Quantity:                 | 1  |
| RAM:                                    | 4 GB DDR4 SDRAM SODIMM 260-pin   |
| Maximum Memory Capacity:                | 32 GB  |
| NetworkTransport Protocol:              | iSCSI<br>L2TP<br>PPTP<br>SMB<br>NFS<br>FTP<br>AFP<br>SSLTLS<br>Telnet<br>SNMP<br>WebDAV<br>SSH<br>SFTP<br>LDAP |
| Data Link Protocol Supports:            | Gigabit EthernetFast<br>EthernetEthernet   |
| Provides Data Channel:                  | SATA   |
| Provides Internal Drive Bay Dimension:  | 2.5"3.5"   |
| Supports RAID Level:                    | JBOD<br>Level 0<br>Level 1<br>Level 10<br>Level 5<br>Level 6   |
| Number of 3.5-inch Hot-Swap Drive Bays: | 4  |
| Interface Provided:                     | USB 3.2 Gen 1: 2x (USB 3.2 (type A))<br>e-SATA: 1x   |

|   |                                    |
|---|------------------------------------|
| LAN: 2x Gigabit EthernetFast EthernetEthernet (RJ-45) |                                    |
| Fans Quantity:  | 2 x 92mm                           |
| Mounting Capability:                                  | Desktop                            |
| External Color:                                       | Black                              |
| Included Accessories:                                 | Power Adapter<br>Quick Start Guide |
| Cable Included:                                       | 2 x Ethernet cables<br>Power Cord  |
| Certifications:                                       | RoHS                               |
| Power Supply:   | Internal<br>AC 100-240 V, 5060 Hz  |
| Maximum Operating Ambient Temperature:                | 40 °C                              |
| Minimum Operating Ambient Temperature:                | 0 °C                               |
| Maximum Operating Humidity:                           | 80 %                               |
| Minimum Operating Humidity:                           | 8 %                                |
| Depth (mm):   | 223 mm                             |